ECO-SERIES LED

Ecological Lighting

ECOLED4

Bright LED source, dimmable, backup



connection: isolated screw connector (240V)

supply: 240Vac (without convertor)

charge: 400mW

dimensions: L: 73mm x H: 73mm x D: 31mm

temperature: ambient temperature wheight: 50 gr - 70 gr (backup model)

installation: ideal for any wall box, with claws

Articles:

ECOLED4W standard LED (old model)

ECOLED4WD standard LED dimmable (with ECODIM)

ECOLED4WS standard LED dimmable/with light sensor (ECODIM)

ECOLED4WB standard LED with backup (20min)

ECOLED4WDB standard LED dimmable with backup (ECODIM)

ECOLED4WSB standard LED dimmable with sensor and backup (ECODIM)

ECOLED4W bright white LED ECOLED4L warm white LED

ECOLED4B blue LED
ECOLED4R red LED
ECOLED4G green LED
ECOLED4Y yellow LED

bright LED light source renewed eco-technology design model with compact dimensions

no need for extra supply (converter) extreme low energy comsumption unlimited life cycle dimmable (ECODIM) or dimmable with sensor (built in) with backup (20min)

ready for installation and finishing mounted in wall box (with claws) ideal for existing installations and new construction application: indication, orientation and ambiance 5 colours available (white, red, green, yellow, blue)

2 year warranty



Special versions on request!!!